

Product Eligibility

DLC Listed LED Tube and Lamp Categories

| Product Type | Product Subtype | DLC [®] Category | DLC Primary Use Designation | Control Tiers Available¨ | Other Requirements |
|----------------------------------|--|---|---|--|---|
| T8 LED | LED Tube, 2 ft. (Type A, B, A/B) | T8 2 ft. | | | N/A |
| | LED Tube, 3 ft. (Type A, B, A/B) | T8 3 ft. | Replacement Lamps (UL Type A, B, A/B) | N/A | |
| Type A, B, A/B | LED Tube, 4 ft. (Type A, B, A/B) | T8 4 ft. | | | |
| | LED Tube, 8 ft. (Type A, B, A/B) | T8 8 ft. | | | |
| T5 LED (4 ft.) Type A, B, A/B | T5 LED (Type A, B, A/B) | T5 4 ft. and T5HO 4 ft. | Replacement Lamps (UL Type A, B, A/B) | N/A | N/A |
| U-Bend LED Type A | U-Bend LED (UL Type A replacement only) | U-Bend Replacement Lamps | Replacement Lamps (Plug & Play UL Type A) | N/A | N/A |
| T8 LED (4 ft.) Type C*** | T8 LED 4 ft. Type C | T8 4 ft. | External Driver (UL Type C) Lamps | N/A | N/A |
| T5 LED (4 ft.) Type C*** | T5 LED 4 ft. Type C | T5 4 ft. and T5HO 4 ft. | | | |
| U-Bend LED Type C*** | T8 U-Bend LED Type C | U-Bend Replacement Lamps | | | |
| | High/Low Bay Mid Output (5,000-10,000 lumens) | - High Bay | High-Bay Aisle High-Bay Luminaires for C&I Buildings Low-Bay Luminaires for C&I | | High/Low Bays must be used for downlighting only. |
| High Bay/ Low Bay* | High/Low Bay High Output (10,000-30,000 lumens) | | | OccupancyDual | Low Bays must be installed at a height of at least 12 feet. High Bays must be installed at a height of at least 20 feet. |
| | High/Low Bay Very High Output (≥30,000 lumens) | | (Excludes Primary Use Designations – All Specialty Products) | • LLLC | |
| | Exterior LED Low Output (250–5,000 lumens) | Low Output Mid Output High Output Very High Output | Architectural Flood and Spot Luminaires Outdoor Pole/Arm-mounted Decorative Luminaires | | N/A |
| Wall Packs, Floods, Shoe | Exterior LED Mid Output (5,000-10,000 lumens) | | Outdoor Pole/Arm-mounted Roadway Luminaires Landscape/Accent Flood and Spot Luminaires Outdoor Full-Cutoff Wall-Mounted Area Luminaires | | |
| Box, Parking Garage & Canopy | Exterior LED High Output (10,000-30,000 lumens) | | Outdoor Non-Cutoff and Semi Cutoff Wall-mounted Area Luminaires Parking Garage Luminaires | Occupancy | |
| | Exterior LED Very High Output (≥30,000 lumens) | | Facking Garage Luminaires Fuel Pump Canopy Luminaires (Excludes Primary Use Designation – All Specialty Products) | | |

Effective January 2024

| Product Type | Product Subtype | DLC [®] Category | DLC Primary Use Designation | Control Tiers Available | Other Requirements |
|--|---------------------------------------|---------------------------|--|---|--------------------|
| Stairwell LED Kit-Mid Output w/ Sensor | Stairwell Kit, Mid Output w/Sensor | Mid Output | Must be installed w/ integrated controls | Occupancy | N/A |
| LED Linear Ambient Strip Wrap | LED Strip Wrap | Linear Ambient | Direct Linear Luminaires | OccupancyDualLLLC | N/A |

DLC Listed LED Troffer Categories

| Product Type | Product Subtype | DLC [®] Category | DLC Primary Use Designation | Control Tiers Available ^{::} | Other Requirements |
|-------------------------------|--|---------------------------|--|---|--------------------|
| LED Troffer and Flat Panel | 1x4, 2x2, 2x4 LED Troffer - Standard / Premium | Troffer | 1x4, 2x2, 2x4 Luminaires for Ambient Lighting of Interior Commercial Spaces | OccupancyDualLLLC | N/A |
| LED Troffer Retrofit Kit | 1x4, 2x2, 2x4 LED Troffer Retrofit Kit - Standard / Premium | Troffer | Linear Retrofit Kits for 1x4, 2x2, 2x4 Luminaires Integrated Retrofit Kits for 1x4, 2x2, 2x4 Luminaires | OccupancyDualLLLC | N/A |

DLC Listed LED Mogul Base LED Replacement Lamp Categories

| Product Type | Product Subtype | DLC [®] Category | DLC Primary Use Designation | Control Tiers Available | Other Requirements |
|----------------|--|---------------------------|--|--|--------------------|
| Interior Mogul | Mogul Interior Low Bay | High Bay | Replacement Lamps for High-Bay Luminaires (Type B) | N/A | N/A |
| Base Lamps | Mogul Interior High Bay | High Bay | Replacement Lamps for Low-Bay Luminaires (Type B) | | N/A |
| | Mogul Exterior Low Output (250–5,000 lumens) | Low Output | Replacement Lamps for Outdoor Pole/ Arm-mounted Area & Roadway Replacement Lamps for Outdoor Full-Cutoff Wall-mounted Area Luminaires Replacement Lamps for Outdoor Pole/ Arm-mounted Decorative Luminaires Type B ONLY | | N/A |
| Exterior Mogul | Mogul Exterior Mid Output (5,000-10,000 lumens) | Mid Output | | N/A | |
| Base Lamps | Mogul Exterior High Output & Very High Output (10,000-30,000 lumens & ≥30,000 lumens) | High Output | | | |

* Source QPLs can be found at the following link: <u>DLC</u>

** Refer to the table below for further information on Control Tiers

*** Per lamp incentive within a qualifying kit

| Control Tier | Required Control Features Listed on DLC | Other Requirements |
|------------------|---|---|
| Occupancy Sensor | Occupancy Sensing: Yes | Must be installed with integrated occupancy sensor |
| Dual Sensor | (Occupancy Sensing: Yes AND Daylight Sensor: Yes) OR Multifunction Sensor: Yes | Must be installed with dual sensor (daylight and occupancy) |
| LLLC/NLC | Integral Control Capability: LLLC | Must be installed with an integrated sensor and be part of a networked and commissioned lighting control system |

WE ARE MASS SAVE*:

