

Product Eligibility

Effective May 22, 2024

DLC Listed LED Tube and Lamp Categories*

Product Type	Product Subtype	DLC* Category	DLC Primary Use Designation	Control Tiers Available**	Other Requirements
T8 LED Type A, B, A/B	LED Tube, 2 ft. (Type A, B, A/B)	T8 2 ft.	Replacement Lamps (UL Type A, B, A/B)	N/A	N/A
	LED Tube, 3 ft. (Type A, B, A/B)	T8 3 ft.			
	LED Tube, 4 ft. (Type A, B, A/B)	T8 4 ft.			
	LED Tube, 8 ft. (Type A, B, A/B)	T8 8 ft.			
T5 LED (4 ft.) Type A, B, A/B	T5 LED (Type A, B, A/B)	T5 4 ft. and T5HO 4 ft.	Replacement Lamps (UL Type A, B, A/B)	N/A	N/A
U-Bend LED Type A	U-Bend LED (UL Type A replacement only)	U-Bend Replacement Lamps	Replacement Lamps (Plug & Play UL Type A)	N/A	N/A
T8 LED (4 ft.) Type C***	T8 LED 4 ft. Type C	T8 4 ft.	External Driver (UL Type C) Lamps	N/A	N/A
T5 LED (4 ft.) Type C***	T5 LED 4 ft. Type C	T5 4 ft. and T5HO 4 ft.			
U-Bend LED Type C***	T8 U-Bend LED Type C	U-Bend Replacement Lamps			
High Bay/ Low Bay*	Low Bay Mid Output (5,000-10,000 lumens)	High Bay	<ul style="list-style-type: none"> High-Bay Aisle High-Bay Luminaires for C&I Buildings Low-Bay Luminaires for C&I (Excludes Primary Use Designations - All Specialty Products)	<ul style="list-style-type: none"> Occupancy Dual LLLC 	<ul style="list-style-type: none"> High/Low Bays must be used for downlighting only. Low Bays must be installed at a height of at least 12 feet. High Bays must be installed at a height of at least 20 feet.
	High Bay High Output (10,000-30,000 lumens)				
	High Bay Very High Output (≥30,000 lumens)				
Wall Packs, Floods, Shoe Box, Parking Garage & Canopy	Exterior LED Low Output (250-5,000 lumens)	<ul style="list-style-type: none"> Low Output Mid Output High Output Very High Output 	<ul style="list-style-type: none"> Architectural Flood and Spot Luminaires Outdoor Pole/Arm-mounted Decorative Luminaires Outdoor Pole/Arm-mounted Roadway Luminaires Landscape/Accent Flood and Spot Luminaires Outdoor Full-Cutoff Wall-Mounted Area Luminaires Outdoor Non-Cutoff and Semi Cutoff Wall-mounted Area Luminaires Parking Garage Luminaires Fuel Pump Canopy Luminaires (Excludes Primary Use Designation - All Specialty Products)	Occupancy	N/A
	Exterior LED Mid Output (5,000-10,000 lumens)				
	Exterior LED High Output (10,000-30,000 lumens)				
	Exterior LED Very High Output (≥30,000 lumens)				

Product Type	Product Subtype	DLC* Category	DLC Primary Use Designation	Control Tiers Available**	Other Requirements
LED Stairwell Kit w/ Sensor	Stairwell Kit, Mid Output w/Sensor	Mid Output	Must be installed w/ integrated controls	Occupancy	N/A
	Stairwell Kit, Low Output w/Sensor	Low Output	Must be installed w/ integrated controls	Occupancy	N/A
LED Linear Ambient Strip Wrap	LED Strip Wrap	Linear Ambient	Direct Linear Luminaires	<ul style="list-style-type: none"> Occupancy Dual LLLC 	<ul style="list-style-type: none"> Linear Ambients Installed height requirement: ≤12 feet

DLC Listed LED Troffer Categories

Product Type	Product Subtype	DLC* Category	DLC Primary Use Designation	Control Tiers Available**	Other Requirements
LED Troffer and Flat Panel	1x4, 2x2, 2x4 LED Troffer - Standard / Premium	Troffer	1x4, 2x2, 2x4 Luminaires for Ambient Lighting of Interior Commercial Spaces	<ul style="list-style-type: none"> Occupancy Dual LLLC 	N/A
LED Troffer Retrofit Kit	1x4, 2x2, 2x4 LED Troffer Retrofit Kit - Standard / Premium	Troffer	<ul style="list-style-type: none"> Linear Retrofit Kits for 1x4, 2x2, 2x4 Luminaires Integrated Retrofit Kits for 1x4, 2x2, 2x4 Luminaires 	<ul style="list-style-type: none"> Occupancy Dual LLLC 	N/A

DLC Listed LED Mogul Base LED Replacement Lamp Categories

Product Type	Product Subtype	DLC* Category	DLC Primary Use Designation	Control Tiers Available**	Other Requirements
Interior Mogul Base Lamps	Mogul Interior Low Bay	High Bay	Replacement Lamps for High-Bay Luminaires (Type B)	N/A	N/A
	Mogul Interior High Bay	High Bay	Replacement Lamps for Low-Bay Luminaires (Type B)		
Exterior Mogul Base Lamps	Mogul Exterior Low Output (250-5,000 lumens)	Low Output	<ul style="list-style-type: none"> Replacement Lamps for Outdoor Pole/ Arm-mounted Area & Roadway Replacement Lamps for Outdoor Full-Cutoff Wall-mounted Area Luminaires Replacement Lamps for Outdoor Pole/ Arm-mounted Decorative Luminaires Type B ONLY 	N/A	N/A
	Mogul Exterior Mid Output (5,000-10,000 lumens)	Mid Output			
	Mogul Exterior High Output & Very High Output (10,000-30,000 lumens & ≥30,000 lumens)	High Output			

* Source QPLs can be found at the following link: [DLC](#)

** Refer to the table below for further information on Control Tiers

*** Per lamp incentive within a qualifying kit

Control Tier	Required Control Features Listed on DLC	Other Requirements
Occupancy Sensor	Occupancy Sensing: Yes	Must be installed with integrated occupancy sensor
Dual Sensor	(Occupancy Sensing: Yes AND Daylight Sensor: Yes) OR Multifunction Sensor: Yes	Must be installed with dual sensor (daylight and occupancy)
LLLC/NLC	Integral Control Capability: LLLC	Must be installed with an integrated sensor and be part of a networked and commissioned lighting control system

WE ARE MASS SAVE®:

