MA Commercial Permit Application Checklist Stretch Code and Municipal Opt-In Specialized Code 2023



	JECT INFORMATION							
	icant Name: Applicant Phone:							
Project Address: Date: Project type: New construction Addition Alteration Changes of Occupancy or Use								
SELI	ECT CODE VERSION							
	Base Code Stretch Code Municipal Opt-in Specialized Code							
SELI	ECT COMPLIANCE PATH (C401.2)							
STRETCH ENERGY CODE PATHS (CMR 225) ¹								
	Prescriptive Path:							
	Provide plans and specifications demonstrating compliance with all measures in Sections C401.3, C402 through C406, and C408.							
	Targeted Performance Path:							
	Provide plans and specifications demonstrating compliance with all measures in Sections C401.3, C402 through C406, C407.1, C408, and select sections of ANSI/ASHRAE/IESNA 90.1-2019 as described in Section C407.1.							
	Relative Performance Path:							
	Provide plans and specifications demonstrating compliance with all measures in Sections C401.3, C402.1.5, C402.2.8, C402.3, C402.4, C402.5, C402.6, C402.7, C403.5, C403.7, C405.2.4, C405.13, C406, C407.2, C408, and ANSI/ASHRAE/IESNA 90.1-2019 using the Appendix G compliance pathway as modified in Section C407.2.							
	Passive House Path:							
	Provide plans and specifications demonstrating compliance with all measures in Sections C401.3, C402.3, C405, C407.3, and C408. Select one option below:							
	Option 1: Phius CORE 2021 or Phius ZERO 2021 Passive Building Standard in accordance with C407.3.2.1							
	 Option 2: Passive House Institute Certified Passive House Standard in accordance with C407.3.2.2 Option 3: Documentation for Design Certified Passive House Projects That Fail Final Certification in accordance with C407.3.2.3 							
	HERS Path:							
	Provide plans and specifications demonstrating compliance with all measures in Sections C401.3, C402.3, C405, C407.4, and C408.							
MUN	ICIPAL OPT-IN SPECIALIZED CODE PATHS (CMR 225, APPENDIX CC)							
	Zero Energy Path:							
	Provide plans and specifications demonstrating compliance with all measures in CC101.4, CC101.5, CC103, and demonstrating that they are Zero Energy Buildings in accordance with Equation CC-1. Mixed Fuel Buildings with any capacity for on-site fossil fuel use shall be pre-wired for future electrification of all fuel uses in accordance with CC105.							
	All-Electric Path:							
	Provide plans and specifications demonstrating compliance with all measures in CC101.4, CC101.5 and CC104.							
	Mixed Fuel Path:							
	Provide plans and specifications demonstrating compliance with all measures in CC101.4, CC101.5,							

¹ For more information about which compliance path to follow, please see the accompanying flowchart for 225 CMR 23: Massachusetts Commercial Stretch Energy Code

STRETCH ENERGY CODE PATHS

Stratch Code Compliance Dath 1. Dreserintive Compliance						
Stretch Code Compliance Path 1: Prescriptive Compliance						
Meets C401.3, C402 through C406, and C408	Envelope, Lighting, and Mechanical Compliance Plan Review Inspection Checklist (Code = 2023 Each Energy Code)					
Section C406 - Must achieve 15 credits in the following categories (# of credits for each category depends on occupancy type):	C406.3 Reduced LP C406.4 Enhanced L C406.5 On-site Sup C406.6 DOAS C406.7 High Efficier C406.8 Enhanced E C406.9 Reduced Air C406.10 Energy Mo C406.11 FDD System C406.12 Efficient Kit C406.13 Type IV He C406.14 Low GWP (C406.2 More Efficient HVAC Performance C406.3 Reduced LPD C406.4 Enhanced Lighting Controls C406.5 On-site Supply of Renewable Energy C406.6 DOAS C406.7 High Efficiency Service Water Heating C406.8 Enhanced Envelope Performance C406.9 Reduced Air Infiltration C406.10 Energy Monitoring System (when not required by C405.12) C406.11 FDD System (when not required by C403.2.3) C406.12 Efficient Kitchen Equipment C406.13 Type IV Heavy Timber Construction C406.14 Low GWP Concrete Mix C406.15 Net Zero GWP Insulation				
Stretch Code Compliance Pat	n 2: Targeted Performand	e (C407.1)				
and select sections of ANS	Meets C401.3, C402 through C406, C407.1, C408, and select sections of ANSI/ASHRAE/IESNA 90.1-2019 Appendix G as described in Section C407.1 The building's heating TEDI and cooling TEI are less than or equal to the values in Table C407.1.1.5					
Attach COMcheck Lighting and Mechanical Compliance Certificates; and a Plan Review Inspection Checklist (Code = 2023 Massachusetts Stretch Energy Code)		Performance Modeling Report with the items described in ANSI/ASHRAE/IESNA 90.1-2019 Appendix G Section G1.3.2 Parts b, g, h, i, j, k, l, n, o, and q, and Section G1.3.3				
Backstop compliance and calculations performed in edition of Massachusetts S Technical Guidance, Attac Performance and Thermal	accordance with latest Stretch Energy Code hment A, Envelope	Completed calculations performed in accordance with latest edition of Massachusetts Stretch Energy Code Technical Guidance, Attachment C, Targeted Performance Simulation Guidelines				
Section C406 - Must achieve 15 credits in the following categories (# of credits for each category depends on occupancy type):	C406.3 Reduced LP C406.4 Enhanced L C406.5 On-site Sup C406.6 DOAS C406.7 High Efficier C406.8 Enhanced E C406.9 Reduced Ai C406.10 Energy Mo C406.11 FDD System C406.12 Efficient Kit	ighting Controls ply of Renewable Energy ncy Service Water Heating nvelope Performance r Infiltration nitoring System (when not required by C405.12) n (when not required by C403.2.3) tchen Equipment avy Timber Construction Concrete Mix				

ENERGY CODE SUPPORT HOTLINE: 855-757-9717

WE ARE MASS SAVE*:

EVERSURCE











Stretch Code Compliance Path 3: Relative Performance (C407.2)								
Meets C401.3, C402.1.5, C4 C402.6, C402.7, C403.5, C C407.2, C408, and ANSI/A the Appendix G compliand Section C407.2	2403.7, C405.2.4, C405 ASHRAE/IESNA 90.1-20	5.13, C406, 019 using	_	Submit mechanical equipment schedules for all air handling equipment with the total design outdoor airflow for each unit				
Backstop compliance and thermal bridge deratin calculations performed in accordance with latest of Massachusetts Stretch Energy Code Technical Guidance, Attachment A, Envelope Performance Thermal Bridge Derating		edition		Completed calculations performed in accordance with latest edition of Massachusetts Stretch Energy Code Technical Guidance, Attachment B, ASHRAE Appendix G Relative Performance Simulation Guidelines.				
An airflow riser diagram with:								
 ☐ The complete project boundary ☐ All supply, exhaust, and return air systems serving the space ☐ A summary of the total outdoor air supplied ☐ The total gross square footage served by the ventilation system ☐ The overall flow rate per area in cfm/ft² Is the building a high glazed wall system (where more than 50% of the above grade wall area of the 								
building thermal envelope is g		c than 50%	01 (11	e above grade wan area of the				
If Yes : Requirements found be met	If No: met							
Section C406 - Must achieve 15 credits in the following categories (# of credits for each category depends on occupancy type): C406.4 Enhanced Lighting Controls C406.5 On-site Supply of Renewable Energy C406.6 DOAS C406.7 High Efficiency Service Water Heating C406.8 Enhanced Envelope Performance C406.9 Reduced Air Infiltration C406.10 Energy Monitoring System (when not required by C405.12) C406.11 FDD System (when not required by C403.2.3) C406.12 Efficient Kitchen Equipment C406.13 Type IV Heavy Timber Construction C406.14 Low GWP Concrete Mix C406.15 Net Zero GWP Insulation								
Stretch Code Compliance Pat	h 4: Passive House Cor	mpliance (C	407.	3)				
Meets C401.3, C402.3, C40	05, C407.3 and C408							
Phius or Passive House Institut	e (PHI) certification in	accordance	e with	n C407.3				
A Phius 2021 (or newer) verification report or a PHPP compliance report which demonstrates project compliance with PHIUS 2021 or PHI performance requirements								
A statement from the Certified Passive House Consultant that the Phius 2021 verification report or PHPP results are "based on plans"								
Evidence of project registration from Phius or PHI or a design certification letter from Phius or from a Certified Passive House Certifier								

ENERGY CODE SUPPORT HOTLINE: 855-757-9717



BERKSHIRE GAS









Stretch Code Compliance Path 5: HERS Index for Multifamily Buildings (C407.4)						
Meets C401.3, C402.3, C405, C407.4 and C408						
HERS Index for Multifamily buildings in accordance with C407.4						
A HERS compliance report with a proposed HERS Index le Table C407.4	A HERS compliance report with a proposed HERS Index less than or equal to the appropriate value in Table C407.4					
A description of the unit's energy features						
A statement that the rating index score is "based on plans" Additional documentation requirements found in C407.4.2.1						
MUNICIPAL OPT-IN SPECIALIZED CODE COMPLIANCE PATHS						
For New R-Use Buildings:						
Dwelling units over 4,000 ft ² in mixed fuel buildings						
☐ Meet the requirements of CC101.3(1) and CC103 OR RE Sec	ction RC102					
Greater than 12,000 ft ² in conditioned floor area						
☐ Meet the requirements outlined in Table CC101.2						
Less than or equal to 12,000 ft ² in conditioned floor area						
☐ Meet the requirements outlined in the Residential Appendi	x RC					
Municipal Opt-In Specialized Code Compliance Path 1: Zero Ei *Mixed Fuel Buildings using this path shall comply with CC105, in addition to						
Meets the requirements of C401.2.1 or C401.2.2, as well as the EV ready space requirements found in C405.13	Meets CC103 and demonstrates that they are Zero Energy Buildings in accordance with Equation CC-1					
Municipal Opt-In Specialized Code Compliance Path 2: All-Ele	_					
Meets the requirements of C401.2.1 or C401.2.2, as well as the EV ready space requirements found in C405.13	Meets CC104 (same as stretch code requirements)					
W	- L (2010)					
Municipal Opt-In Specialized Code Compliance Path 3: Mixed *When not complying with the Zero Energy pathway	Fuel (CCIO5)					
Meets the requirements of C401.2.1 or C401.2.2, as well as t requirements found in C405.13	the EV ready space					
Meets CC106, which requires wiring for future electrification equipment, and other combustion equipment	on in water heating, cooking, clothes drying					
Construction documents showing electric HVAC retrofit design prepared by the HVAC engineer in accordance with CC106.1.6.1, including:						
Future replacement of combustion equipment-based HVA system	C system with an equivalent all electric					
Combustion equipment to be replaced						
Tuture electric equipment						
Supporting electrical, structural, and architectural infrastructure to be installed during building construction						
Space allotments for future equipment						

ENERGY CODE SUPPORT HOTLINE: 855-757-9717













REQUIRED CONSTRUCTION DETAILS.....

Indicate primary locations within the construction documentation of the following information:

	Drawing Page(s)	Specification(s)
BUILDING THERMAL ENVELOPE		
Cross section showing insulation R-values and materials for each building thermal envelope component		
Cross section showing air barrier/air sealing details		
Fenestration U-factors and solar heat gain coefficients (SHGCs)		
MECHANICAL SYSTEMS		
Design criteria		
Equipment types, sizes and efficiencies		
Controls description		
Pipe insulation		
Fan motor horsepower (hp) and controls		
Economizer description		
Duct sealing, insulation and location		
Service water heating systems		
Pipe insulation and location		
LIGHTING		
Lighting fixture schedule with wattage and control narrative		
Location of daylight zones of floor plans		
OTHER COMPLIANCE ITEMS		
Appendix CB or potential solar zone area in accordance with Appendix CC		
EV Ready Spaces locations in accordance with C405.13		
COMcheck Envelope, Lighting, and Mechanical Compliance Certificates; and a Plan Review Inspection Checklist		
RELATIVE PERFORMANCE PATH		
Mechanical equipment schedules		
An airflow riser diagram		
MIXED FUEL BUILDINGS FOLLOWING APPENDIX CC		
Electric HVAC retrofit design		

☐ Commissioning Plan - Preliminary Commissioning Plan from commissioning agent

ENERGY CODE SUPPORT HOTLINE: 855-757-9717











